**SMART**®

Specifications

—

Active USB extension cable
Model USB-XT

Overview

You can use a maximum of three active USB extension cables to extend a 16' (5 m) USB cable to 64' (20 m).

For more information about extending USB connections with the active USB extension cable, see *Extending USB connections* (smarttech.com/kb/099641).

> **Notes**
>
> - If you connect more than three active USB extension cables, you can exceed the USB specification limit of five hubs if your computer or a connected device has an internal hub.
> - The USB-XT extension cable is compatible with all of SMART's currently supported USB-connected products. It supports a maximum communication speed of 480 Mpbs (High-Speed).

Dimensions and weights*

Length	16' (5 m)
Module size	2 3/8" × 5 3/8" × 1" (60 mm × 135 mm × 27.6 mm)
Weight	5.3 oz (150 g)
Shipping weight	1 lb. (450 g)
Shipping size	2" × 10 1/2" × 9 3/8" (508 mm × 267 mm × 238 mm)

Standard features

USB device support	USB 2.0 high speed (up to 480 Mbps) and USB 1.1 (12 Mbps) devices Recognized as one USB hub by the computer's operating system
Compatibility	Windows® operating systems, macOS operating system software and Linux® operating systems
Connectors	One USB-A receptacle One USB-A plug

*All dimensions ± 1/8" (0.3 cm).

Storage and operating requirements

Power supply	Bus powered from upstream hub or computer interface
Power consumption	5 mA maximum, 3 mA typical
Operating temperature	32°F to 104°F (0°C to 40°C)
Storage temperature	–40°F to 185°F (–40°C to 85°C)

Certification and compliance

Regulatory certification	FCC and CE Class B
Environmental compliance	RoHS (Europe) and WEEE

Purchasing information

Order number

USB-XT	Bus powered active USB extension cable
Warranty	One-year limited equipment warranty